



NEW HOLLAND TM7000

TM7000 EXITUS | TM7000 PLATFORM



SPECIFICATIONS

MODEL		TM7010 EXITUS	TM7020 EXITUS	TM7030 EXITUS	TM7040 EXITUS
Engine					
Make		New Holland	New Holland	New Holland	New Holland
Rated rpm	(rpm)	2,200	2,200	2,200	2,200
Power @ rated rpm	(kW/hp)	104/141	112/149	124/168	132/180
Torque at 1400 rpm	(nm)	610	620	720	733
Aspiration		Turbo intercooler	Turbo intercooler	Turbo intercooler	Turbo intercooler
Number of cylinders	(n.)	6	6	6	6
Transmission					
Type		Synchro Shuttle™	Synchro Shuttle™	Synchro Shuttle™	Synchro Shuttle™
Speeds (forward x reverse)		16x16	16x16	15x12	15x12
Power take-off					
Actuation		Electro-hydraulic	Electro-hydraulic	Electro-hydraulic	Electro-hydraulic
Rpm	(rpm)	540/1,000	540/1,000	540/1,000	540/1,000
Hydraulics					
Pump		Gear type	Gear type	Gear type	Gear type
Flow capacity	(l/min)	57	57	120	120
One-way pump flow	(l/min)	53	53	60	60
Lift-O-Matic™		●	●	●	●
Lifting capacity at 610 mm from the lift eye, with 2 auxiliary cylinders	(kg)	6,475	6,475	6,475	6,475
Fuel tank capacity					
Main fuel tank	(L)	270	270	270	270
Auxiliary fuel tank	(L)	110	110	110	110
Operator comfort					
Air conditioner		●	●	●	●
Ergonomic control arrangement		●	●	●	●
Adjustable seat with seat belt		●	●	●	●
Tilting rear window		●	●	●	●

● Standard

MODEL		TM7010 PLATFORM	TM7020 PLATFORM	TM7030 PLATFORM	TM7040 PLATFORM
Engine					
Make		New Holland	New Holland	New Holland	New Holland
Rated rpm	(rpm)	2,200	2,200	2,200	2,200
Power @ rated rpm	(kW/hp)	104/141	112/149	124/168	132/180
Torque at 1400 rpm	(nm)	610	620	720	733
Aspiration		Turbo intercooler	Turbo intercooler	Turbo intercooler	Turbo intercooler
Number of cylinders	(n.)	6	6	6	6
Transmission					
Type		Synchro Shuttle™	Synchro Shuttle™	Synchro Shuttle™	Synchro Shuttle™
Speeds (forward x reverse)		16x16	16x16	15x12	15x12
Power take-off					
Actuation		Electro-hydraulic	Electro-hydraulic	Electro-hydraulic	Electro-hydraulic
Rpm	(rpm)	540/1,000	540/1,000	540/1,000	540/1,000
Hydraulics					
Pump		Gear type	Gear type	Gear type	Gear type
Flow capacity	(l/min)	57	57	120	120
One-way pump flow	(l/min)	53	53	60	60
Lift-O-Matic™		●	●	●	●
Lifting capacity at 610 mm from the lift eye, with 2 auxiliary cylinders	(kg)	6,475	6,475	6,475	6,475
Fuel tank capacity					
Main fuel tank	(L)	270	270	270	270
Auxiliary fuel tank	(L)	110	110	110	110
Operator comfort					
ROPS frame with canopy		●	●	●	●
Ergonomic control arrangement		●	●	●	●

● Standard



YOUR SUCCESS - OUR SPECIALTY



INTERNATIONAL

AT YOUR OWN DEALER

Visit our website: www.newholland.com - Send us an e-mail: International@cnh.com

The data indicated in this folder are approximate. The models described here can be subjected to modifications without any notice by the manufacturer. The drawings and photos may refer to equipment that is either optional or intended for other countries. Please apply to our Sales Network for any further information. Published by CNH INTERNATIONAL SA. Communications & Advertising. Bts Adv. - Printed in Italy - 06/11 - TP01 - (Turin) - IR0104N/INB