



NEW TS6 SERIES TRACTORS

110 to 139 RATED HP

TS6.110 | TS6.120 | TS6.125 | TS6.140



SPECIFICATIONS

MODELS		TS6.110	TS6.120	TS6.125	TS6.140
Engine					
Engine type		4 cylinder		6 cylinder	
Make / model		NH FPT / NEF			
Displacement (L)		4.5		6.7	
Aspiration		Turbo intercooled			
Emissions certification		Tier 3			
Rated power (kW/hp)		82/110	88/118	93/124	104/139
Power (kW/hp)		71/95	74/99	77/105	88/118
Maximum torque @ 1250rpm (Nm)		510	515	555	625
Forward speed					
30 kph version (18.4R38) (kph)				31.7	
40 kph version (18.4R38) (kph)				40.5	
Transmission					
8 x 8 synchronized shuttle w/ left hand shuttle				●	
8 x 8 Hydraulic shuttle w/ left hand shuttle				○	
16 x 8 Hi-Low Hydraulic shuttle w/ left hand shuttle				○	
Creep option (all transmissions)				○	
PTO (Fully independent wet clutch)					
Speed Std. / Opt.		540 / 540-1000		540-1000 / -	
3 point hitch					
Category				II	
Draft sensing				Top link	
ASAE				●	
Lift capacity (OECD@610mm) (kg)				2410	
Option 1 ASAE lift capacity (OECD@610mm) (kg)				3639	
Option 2 ASAE lift capacity (OECD@610mm) (kg)				4647	
Hydraulics					
Standard pump flow (L/min)				49	
"High Flow" pump (L/min)				83	
Steering					
Steering pump flow (L/min)				34	
Wheelbase					
2WD (mm)		2571		2631	
4WD (mm)		2520		2627	
Axles					
Front 2WD adjustable tread width (mm)				1422-2032	
Front 4WD adjustable tread width (mm)				1626-2032	
Rear adjustable tread width (Flange axle) (mm)				1626-2032	
Front axle turn angle (2WD / 4WD) (°)				55	
Weight					
Minimum shipping weight:					
2WD ROPS (kg)		3413		3613	
4WD ROPS (kg)		3678		3878	
2WD cab (kg)		3588		3788	
4WD cab (kg)		4013		4213	
Dimensions*					
Overall length:					
2WD (mm)		4115		4191	
4WD (mm)		4216		4293	
Height, top of ROPS (mm)				2959	
Height, top of cab (mm)				2816	
Height, top of exhaust (mm)				2959	
Key configurations					
2WD ROPS				○	
4WD ROPS				●	
2WD cab				○	
4WD cab				○	
Hi clearance (4WD only)		-	○		-

● Standard ○ Optional - Not available
 * Dimensions shown are with 18.4x34 rear tires



New Holland prefers **AMBRA** lubricants

AT YOUR OWN DEALER



YOUR SUCCESS - OUR SPECIALTY



INTERNATIONAL

Visit our website: www.newholland.com - Send us an e-mail: international@newholland.com

The data indicated in this folder are approximate. The models described here can be subjected to modifications without any notice by the manufacturer. The drawings and photos may refer to equipment that is either optional or intended for other countries. Please apply to our Sales Network for any further information. Published by CNH INTERNATIONAL SA. Communications & Advertising. Bts Adv. - Printed in Italy - 07/12 - TP01 - (Turin) - IR2104N/INB