



Agrotrac .	<b>表表表</b> 語	610	620
Homologated power (ECE R24)	kW/hp	120/163	53/72
Homologated power (2000/25 EC)	kW/hp	103/140	120/163
Max. torque	Nm	510	624
Cylinders/displacement	n°/cc	6/6,000	
. Lifting capacity	kg	7,000	
Width min	mm	2,170	2,216
Weight with cab	kg	5,450	5,700

## 610 - 620 AGROTRAC

## THE PERFECT TRACTOR FOR TRANSPORT AND FIELD WORK.

The DEUTZ-FAHR Agrotrac range is designed and built to tackle a wide variety of farm work. Because they are so productive and versatile, Agrotrac tractors are perfectly at ease with demanding open field work, even carrying implement combinations. They also excel in fast transport. A good power-to-weight ratio, correct weight distribution, and advanced technical specifications guarantee maximum efficiency under all conditions, while intelligent ergonomics and an intuitive control layout make them easy to operate from the moment you climb aboard.

## THE FEATURES

- SDF series 1,000 Tier III engines, 6 cylinders turbo intercooler
- Electronically controlled fuel system
- ≥ 24 FWD + 12 REV synchronised gearbox
- Excellent Driving position with cab suspended on silent block
- High efficiency transmission
- 240 litres fuel tank capacity
- 7,000 kg max. lifting capacity with 68 l/min pump delivery



Electronic engine control ensures optimal injection efficiency, stable performance during all operating conditions. Engine speed programming feature allows optimum work setting of engine rpm.



The cab roof incorporates a large glass hatch so that front loading can be performed in complete safety with full visibility.