



| Agrovector | | 29.6 | 29.6 LP | 35.7 | 37.6 | 37.7 |
|---------------------------------|-------|--------|---------|-------|-------|------|
| Max. power at 2,200 1/min | kW/hp | 75/102 | | | | |
| Max. lifting force | kg | 2,900 | | 3,500 | 4,000 | |
| Lifting capacity at max. height | kg | 2,420 | | 2,600 | 4,000 | |
| Max. lifting height | m | 5.80 | | 6.90 | 7.90 | 9.00 |
| Height of the machine | mm | 2,180 | 1,989 | 2,370 | 2,450 | |
| Width of the machine | mm | 2,040 | | 2,330 | 2,380 | |
| Turning circle | m | 3.65 | | 3.90 | 4.00 | |
| Unladen weight with pallet fork | kg | 6,060 | | 7,400 | 8,100 | |

29.6 - 29.6 LP - 35.7 - 37.6 - 37.7 AGROVECTOR

THE MASTER LOADER.

With the Agrovector DEUTZ-FAHR offers a universally versatile telescopic loader for all applications with a wide range of attachments for many agricultural jobs. The powerful hydraulic system and the economical engines make the Agrovector an irreplaceable aid for the widest range of assignments.

THE FEATURES

- ▶ Deutz Tier III A or B 4-cylinder turbo engines with high-pressure fuel injection system
- ▶ Double-extension telescopic boom in high strength steel
- ▶ 2-speed hydrostatic transmission; maximum speed of 35 km/h
- ▶ 4-speed powershift transmission with torque converter; maximum speed of 40 km/h (37.6 – 37.7)
- ▶ Closed centre Load Sensing hydraulic system with variable displacement pump (37.6 – 37.7)
- ▶ Reversible fan for improved cooling efficiency
- ▶ On-board computer with integrated diagnostic system
- ▶ Joystick with proportional electronic control
- ▶ Long wheelbase for greater stability and agility
- ▶ Wide choice of attachments for all types of applications
- ▶ Low-profile version



The electronic alarm indicator provides a visual and acoustic alarm when an overload is reached.



Every function in sight: The central control and display terminal provides information about all the operating statuses.